



RFW 24x36x30 T15

RFW 24x36x30 T22

RFW 24x36x30 Rectangular Flared Wall Vault



Specs and Techs: RFW 24x36x3

RFW 24x36x30		
Dimensions	24"x36"x30"	
Weight	RFW 24x36x30 T15 154.4lbs [70kg]	RFW 24x36x30 T22 242.5lbs [110kg]
Load Class	RFW 24x36x30 T15 ANSI 77: Tier 15 (100 kN)	RFW 24x36x30 T22 ANSI 77: Tier 2 (150 kN)
Branding	As per customer requirement	

Description:

The RFW 24x36x30 vaults are purpose designed access vaults for accessing medium to high density utility networks. The vaults have a flared wall design which offers stability in the installation process, economy in the transport and storage process, and the range caters for various vertical load applications. The vaults are manufactured from a mix of various composite material technologies and as a result are light in weight.

Features and Benefits: RFW 24x36x30

- **Medium/High Density Traffic Installations:** Ideal for medium to high utility density installations.
- **Lightweight Design:** Manufactured from lightweight, high strength composite materials.
- **Tapered vault design:** Designed for higher cable slack management with larger fiber counts and enclosures.
- **Harsh Environment:** Designed to operate in environments with temperatures as low as -40°F [-40°C].
- **Transport Efficiency:** The unit stacks, offering economic transport and storage practices.
- **Fire Retardancy:** Can be formulated to comply with UL94 V-0.
- **Quality Manufacturing:** Manufactured in an ISO 9001 certified facility and tested in accordance with relevant national and international standards, ensuring quality and reliability.

For more information on BABA compliance please visit: <https://www.infratecgroup.com/baba>

Revision: July 2025