



## Specs and Techs: 320T Access Point / Boundary Box

### Description:

The axS 320T is a purpose-designed, robust mini access box or boundary box ideal for low fiber count connections. Engineered for reliability and efficiency, the axS 320T is perfect for connecting Multi-Dwelling Units (MDUs) or individual clients to the network. With its compact and durable construction, it ensures seamless integration into various network infrastructures while maintaining high performance and ease of use.

### Features and Benefits:

- **Smart Monitoring Options:** axSCHAMBERS™ are available with RAMAC™ smart monitoring technology options for enhanced performance and monitoring capabilities.
- **Low Density Traffic Installations:** Ideal for low-density communication traffic areas, with the ability to connect up to 12 connections depending on the splitter configuration.
- **Flexible Installation:** The chamber and base sections can be split allowing for easy installation over existing networks.
- **Compact Design:** Features a small footprint with a compact design making it space efficient.
- **Tool-free Assembly:** No tools required for assembly, the axS 320T's press-on clips are used to connect the base and chamber sections.
- **Sealed Duct Ports:** Duct ports are equipped with rubber grommets to interface with multiduct and/or Microduct without the need for additional sealants.
- **Transport Efficiency:** The knock-down design allows for high packing density, resulting in transport cost savings.
- **Convenient Lid Design:** The hinge less, slide-in lid with nylon lanyard ensures easy access and secure closure.
- **Locking Options:** Alternative locking options available.
- **Quality Manufacturing:** Manufactured in an ISO 9001 certified facility and tested in accordance with relevant national and international standards, ensuring quality and reliability.

	axS320T		
<b>Dimensions</b>	320mmx337mmx310mm (12.6"x13.3"x12.2")		
<b>Weight</b>	2,5kg (5.5 lb)		
<b>Load Class</b>	SANS 1882: LD (7kN) EN124: A15 (1.5T) ANSI 77: LD (13.3kN)		
<b>Branding</b>	As per customer requirement		
<b>Loading Qty*</b>	<b>18m link</b>	<b>6m (20') Container</b>	<b>12m (40') Container</b>
	3600 Knock-Down	1800 Knock-Down	3600 Knock-Down

\*Loading quantities are theoretical and may differ slightly.