



## axS 320T-S Access Point / Boundary Box



### Specs and Techs: axS 320T-S

axS 320T-S	
<b>Dimensions</b>	13,9"x14,6"x9" (352mmx370mmx288mm)
<b>Load Class</b>	ANSI 77: Light Duty (13.3kN) EN124: A15 (15.0kN)
<b>Branding</b>	As per customer requirement

### Description:

The axS 320T-S is a purpose-designed, robust mini access box or boundary box ideal for low fiber count connections. Engineered for reliability and efficiency, the axS 320T-S is perfect for connecting Multi-Dwelling Units (MDUs) or individual clients to the network. Featuring a single-shot construction without a base to ensure seamless integration over existing network infrastructures. With its compact and durable construction, the axS 320T-S maintains high performance and ease of use while providing reliable network connectivity.

## Features and Benefits: axs 320T-S

- **Smart Monitoring Options:** axsCHAMBER™ are available with RAMACT™ smart monitoring technology options for enhanced performance and monitoring capabilities.
- **Low Density Traffic Installations:** Ideal for low-density traffic areas, with the ability to connect to 12 clients depending on the splitter configuration.
- **Flexible Installation:** Designed for easy installation over existing and new networks.
- **Compact Design:** Features a low footprint with compact design making it space efficient.
- **Tool-free Assembly:** Easy assembly process with no tools required due to the simplicity of the product.
- **Transport Efficiency:** Enhanced stackability for cost-effective transportation
- **Secured Lid Design:** Hinged, slide-in lid with 1/4" single stainless-steel bolt-down locking mechanism for secure and easy access.
- **Quality Manufacturing:** Manufactured in an ISO 9001 certified facility and tested in accordance with relevant national and international standards, ensuring quality and reliability.

For more information on BABA compliance please visit: <https://www.infratecgroup.com/baba>

Revision: July 2025