



**axS 600R**



**axS 600RXL**

## Specs and Techs: axS 600R Access Chamber

### Description:

The axS 600R is a modular composite solution offering the network builder unsurpassed flexibility, performance and economy. The Chamber section is an assembly of quarter segments.

### Features and Benefits:

- axSCHAMBERS™ are available with RAMAC™ Smart Monitoring Technology options.
- Interoperable with our selection of CNKT Fibre Splice Closure Range of Products.
- Modern composite design ensures high strength / low weight for installation cost savings.
- Ideal for high fibre traffic installations – up to 2 × 144 or 4 × 48 Fibre Closures.
- Splitable porting panels uniquely allow retrofitting to existing networks or new builds alike.
- Easy assembly with basic hand tools only.
- Unique multi-port knockouts give industry leading interface with all Duct and Multiduct options.
- Modular design allows various depth configurations.
- DMC cover eliminates the threat of theft as it has no "scrap value".

## Additional Feature – 100mm xtnd-IT Spacer Ring

### Advantages of the axSCHAMBER™ xtnd-IT Ring:

- The chamber can be scalable and made deeper, allowing for deeper statutory trenching requirements.
- The addition of the ring will allow for further microduct and cable slack management capacity.
- The ring can be retrofitted to already installed chambers, in the event of new roads, paving or other infrastructure are overlaid.
- Full range of loading options available.
- Modular knock-down design offers high packing density for transport savings.

	<b>axS 600R</b>	<b>axS 600RXL</b>
<b>Dimensions</b>	Ø750mmx720mm (29.5" x 28")	Ø750mmx820mm (29.5" x 32")
<b>Weight</b>	41kg (90.4lbs)	44 Kg (97lbs)
<b>Load Class</b>	SANS Medium Duty (40kN) SANS Heavy Duty (135kN) EN124: B125 (12.5T) & C250 (25 T) ANSI: Tier 22 (15.3T)	SANS Medium Duty (40kN) SANS Heavy Duty (135kN) EN124: B125 (12.5T) & C250 (25 T) ANSI: Tier 22 (15.3T)
<b>Branding</b>	As per customer requirement	As per customer requirement