



axS 900R450



axS 900R900



axS 900R1350

Specs and Techs: axS 900R Access Chamber

Description:

The axS 900R is a modular composite solution offering the network builder unsurpassed flexibility, performance and economy. The Chamber section is an assembly of multiple layers of quarter segments (see height options).

Features and Benefits:

- axS CHAMBERS™ are available with RAMACT™ Smart Monitoring Technology options
- Interoperable with our selection of CNKT Fibre Splice Closure Range of Products
- Modern composite design ensures high strength / low weight for installation cost savings.
- Ideal for high fibre traffic installations – up to 4 × 144 Fibre Closures.
- Splittable porting panels uniquely allow retrofitting to existing networks or new builds alike.
- Easy assembly with basic hand tools only.
- Unique multi-port knockouts give industry leading interface with all Duct and Multiduct options.
- Modular design allows various depth configurations (see height options).
- DMC cover eliminates the threat of theft.
- Full range of loading options available.
- Modular knock-down design offers high packing density for transport savings.

	axS 900R450	axS 900R	axS 900R1350
Dimensions	Ø950mmx457mm (37" x 18")	Ø950mmx1000mm (37" x 39.4")	Ø950mmx1350mm (37" x 53.2")
Weight	82Kg (181lbs)	98Kg (216 lbs)	114Kg (252lbs)
Load Class	SANS Medium Duty (42kN) EN124: B125 (12.5T) ANSI: Tier 22 (15.3T)	SANS Medium Duty (42kN) EN124: B125 (12.5T) ANSI: Tier 22 (15.3T)	SANS Medium Duty (42kN) EN124: B125 (12.5T) ANSI: Tier 22 (15.3T)
Branding	As per customer requirement	As per customer requirement	As per customer requirement

Loading Quantities (product code)	18m Link	6m (20') Container	12m (40') Container
axS 900R 450	On request	On request	On request
axS 900R 900	64 Units (Assembled)	54 Units (Knock-Down)	108 Units (Knock-Down)
axS 900R 1350	On request	On request	On request