



Specs and Techs: 320T-S Access Point / Boundary Box

Description

The axs 320T-S is a purpose-designed, robust mini access box or boundary box ideal for low fiber count connections. Engineered for reliability and efficiency, the axs 320T-S is perfect for connecting Multi-Dwelling Units (MDUs) or individual clients to the network. Featuring a single-shot construction without a base to ensure seamless integration over existing network infrastructures. With its compact and durable construction, the axs 320T-S maintains high performance and ease of use while providing reliable network connectivity.

Key Features

- **Smart Monitoring Options:** Access chambers available with RAMAC™ smart monitoring technology options for enhanced performance and monitoring capabilities.
- **Low Density Traffic Installations:** Ideal for low-density traffic areas, with the ability to connect up to 12 clients depending on the splitter configuration.
- **Flexible Installation:** Designed for easy installation over existing and new networks.
- **Compact Design:** Features a low footprint with compact design making it space efficient.
- **Tool-free Assembly:** Easy assembly process with no tools required due to the simplicity of the product.
- **Transport Efficiency:** Enhanced stackability for cost-effective transportation
- **Secured Lid Design:** Hinged, slide-in lid with 1/4" single stainless-steel bolt-down locking mechanism for secure and easy access.
- **Quality Manufacturing:** Manufactured in an ISO 9001 certified facility and tested in accordance with relevant national and international standards, ensuring quality and reliability.

Performance

- Light weight construction enables easy handling and installation.
- UV stabilised for prolonged outdoor exposure
- Resistant to moisture, corrosion and biological degradation
- Resistant to a wide range of dilute acids, alkalis and salts commonly encountered in underground environments
- Suitable for a wide range of service temperatures typical of outdoor installations
- Manufactured from durable engineering-grade materials designed for long service life with minimal maintenance.

	axs320T-S
Dimensions	Daylight Opening: 185mmx185mm (7.3"x7.3") Footprint: 352mmx370mmx288mm (13,9"x14,6"x9")
Load Class	SANS 1882: LD (7kN) EN124: A15 (1.5T) ANSI 77: LD (13.3kN)
Branding	As per customer requirement